

Brominator - High Capacity Feeders



Vent valve bleeds air to ease lid removal.

Safety lock-ring spins off, freeing lid and providing easy access. Safety snap-lock provides secure seal.

Screen and check ball are easy to reach for cleaning and periodic maintenance.

Flow-through circulation allows maximum output of sanitised water.

External dial control for easy flow rate adjustment.

Drain valve makes it easy to drain feeder for safe recharging and winterising.

Unions are included for easy installation.

These heavy-duty, high capacity feeders provide automatic sanitisation for pools of up to 1,260m³.

They are designed for off-line hard plumbing installations using 1" PVC pipe, and are available in three sizes.

Standard features include:

- Heavy-duty control valve for accurate feed rate adjustment.
- Drain valve allows easy draining for safe recharging or winterising.
- Standard threaded inlet and outlet fittings included for easy installation.
- No special venting required.
- Completely enclosed system, no escaping fumes.
- Easy access for recharging and servicing.
- Designed for ease-of-use and simple maintenance.

Off-Line Feeder Installation

The INLET control valve side of the feeder connects to the plumbing on the discharge side of the pump, before the filter. The OUTLET side of the feeder connects to the pool return line after the filter and/or heater, pool cleaner, diverter valves or any other installed equipment.

Installation of a corrosion-resistant check valve, such as Pentair's H-RA-172288, between the feeder inlet and outlet and the equipment is recommended to check backflow of chemicals. This helps ensure equipment longevity.

Model Part Number	HC3315 H-RA-R171215	HC3330 H-RA-171230	HC3340 H-RA-171240
Width	203mm	203mm	203mm
Height	546mm	994mm	1264mm
Depth	381mm	381mm	381mm
Maintenance Clearance	578mm	1.026mm	1.296mm
Capacity (kg)	6,8kg	13,6kg	18kg
Maximum Output Rate, Chlorine (kg/h)	0,55kg	0,9kg	1,88kg
Maximum Pool Size, Chlorine (m ³)	370m ³	608m ³	1.260m ³
Maximum Output Rate, Bromine (kg/h)	0,26kg	0,52kg	0,79kg
Maximum Pool Size, Bromine (m ³)	74m ³	156m ³	234m ³
Maximum working pressure	3,45bar		